



ELF SCOOTER² STREET

2-stroke motor oil

KEY DATA

- **SCOOTER RANGE**



- **2-STROKE MOTOR OIL**
- **SYNTHETIC BASED**

- **INTERNATIONAL STANDARDS**

- ✓ API TC
- ✓ JASO FD
- ✓ ISO L-EGD

- **LEVEL**



APPLICATIONS

ELF SCOOTER² STREET is a lubricant that is particularly recommended for all types of 2-stroke scooters and mopeds, in compliance with API TC, JASO FD and ISO L-EGD international standards.

ELF SCOOTER² STREET is especially suitable for the requirements of urban traffic (stops and starts) and rural travelling conditions (intercity). **ELF SCOOTER² STREET**'s composition is compatible with lead-free fuels. The product is pre-diluted and therefore suitable for separate lubrication and mixing. The oil content needs to be dosed according to the manufacturers' recommendations.

ELF SCOOTER² STREET is reinforced with synthetic base oils to provide extra protection for the engine and its peripherals.

ELF SCOOTER² STREET's homogeneous mixture ensures a constant lubrication quality.

CUSTOMER BENEFITS

- **Detergence and anti-clogging of transfer ports:** The strong and efficient detergent additives ensure cleanliness of the timing system.
- **Clean combustion and anti-deposit technology:** The mixture combusts completely, ensuring that all the additives and base oils are thermally broken down. The detergent additives work on all deposits that are formed, ensuring that the engine retains its original efficiency. **ELF SCOOTER² STREET**'s innovative formula provides results that are far above the benchmark indices required by the international JASO FD and ISO-L-EGD specifications.
- **Reduction in exhaust smoke:** The special additives it contains help reduce emissions.



CHARACTERISTICS*

Test	Unit	Result
Density at 15°C	kg/m ³	869
Sulphated ash content	% weight	0.07
Kinematic viscosity at 100°C	mm ² /s	10.9
Pour Point	°C	-21
OC Flash Point	°C	114
Colour	-	Blue

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's user guide should be checked. This lubricant has been designed to lubricate 2-stroke engines fitted with independent greasing systems or for use as part of a mixture in percentages recommended by the manufacturer.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.com.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL Lubrifiants
Immeuble Le Spazio
562, avenue du Parc de l'île
92029 Nanterre Cedex
France

Last update of this datasheet: 05/2014

ELF SCOOTER² STREET



Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubrifiants.total.fr.